

# Specification sheet: Cresco 10SWG



**Product Description:**  
Impellor Style Pedestrian operated spreader

	Descriptions	Technical Specification
	<b>Framework</b>	Powder coated steel
	<b>Wheels</b>	2 X moulded tread wide wheels 24 cm high by 7 cm across
	<b>Axle</b>	Powder coated steel
	<b>Gear box</b>	Encased crown and pinion, zero maintenance gears. Made from composite material, hard-wearing construction with extra-large bushings
	<b>Hopper</b>	30 litre capacity. Up to maximum 35kg weight bearing, 3 drop hole
	<b>Impellor</b>	Shaped 21cm four fin impellor. Provides spread width of between 2.5 and 6 metres
	<b>Shutter Plate (Summer Slider)</b>	Hard wearing multifunctional interchangeable slider. Offering left and right spread pattern adjustment and a border control system
	<b>Shutter Plate (Winter slider)</b>	Hard wearing multifunctional interchangeable slider. Providing high output and spread width reduction system
	<b>Linkage</b>	Solid steel rod
	<b>Agitator</b>	6.0 cm pin through agitator
	<b>On/off Control Bezel</b>	1 to 20 scale with T bar style lever, with rate setting lock
	<b>Handlebar</b>	Cushioned grip over loop style easy fold away handle
	<b>Weight Empty</b>	5.5 kg
	<b>Dimensions</b>	Height 61 cm width 51 cm
	<b>Packaging</b>	Assembled
	<b>Pelleting</b>	120 cm by 100 cm UK deliveries, 120 cm by 80 cm EU deliveries. Euro plastic pallets
	<b>Box dimensions and weights</b>	Assembled 65 cm by 53 cm by 42 cm, 6.3 kg
	<b>Pallet configuration (units per pallet)</b>	U.K. Assembled 18 E.U. Assembled 10
	<b>Guarantee/Warranty</b>	2-year limited warranty
	<b>Box information</b>	QR code and Bar code, full instruction and how to use manual. Available in different languages