

# Specification sheet: Cresco 25SW



**Product Description:**  
Impellor Style Pedestrian operated spreader

	Descriptions	Technical Specification
	<b>Framework</b>	Painted steel with stainless fasteners
	<b>Wheels</b>	2x Pneumatic treaded tyres with inner tubes 13 X 5.00 - 6
	<b>Axle</b>	Stainless steel
	<b>Gear box</b>	Encased crown and pinion, zero maintenance gears. Manufactured in a composite material, ultra-hard-wearing construction with advanced performing bushings
	<b>Hopper</b>	40 litre capacity with front lift point, up to a maximum 45kg weight bearing. 3 drop hole outlets
	<b>Impellor</b>	24 cm shaped four fin impellor provides spread widths of between 2.5 and 6 metres
	<b>Shutter plate (Summer Slider)</b>	Hard wearing multifunctional interchangeable slider. Providing left & right side spread pattern adjustments and a border control system
	<b>Shutter plate (Winter slider)</b>	Hard wearing multifunctional interchangeable slider. Providing high output, wide spread and spread width reduction system
	<b>Linkage</b>	Solid steel rod
	<b>Dual-Agitator</b>	6.0 cm pin through agitator x 2
	<b>On/off control bezel</b>	1 to 20 scale with T bar style lever and rate setting lock mechanism
	<b>Handlebar</b>	Cushioned loop handle
	<b>Weight empty</b>	14 kg
	<b>Dimensions</b>	Width 60 cm height 74 cm length 120 cm
	<b>Packaging</b>	Both assembled and flat pack available, brown cardboard carton
	<b>Pelleting</b>	120 cm by 100 cm UK deliveries, 120 cm by 80 cm EU deliveries Euro plastic pallets
	<b>Box dimensions and weight</b>	Flat pack 45 cm by 75 cm by 57 cm 14.3 kg Semi assembled 75 cm by 58 cm by 55 cm 14.5 kg
	<b>Pallet configuration (units per pallet)</b>	U.K. Flat pack 9 Units, assembled 6 Units E.U. Flat Pack 8 Units, assembled 6 Units
	<b>Guarantee/warranty</b>	2-year limited warranty
	<b>Box information</b>	QR code and Bar code, full instruction and how to use manual. Available in different languages