Specification sheet: Cresco 30SWS





Product Description:Impellor Style Pedestrian operated spreader

| | Descriptions | Technical Specification |
|----------|--|---|
| | Framework | Stainless steel with stainless fasteners |
| | Wheels | 2x Pneumatic treaded tyres with inner tubes 13 x 5.00 - 6 |
| F + 4 | Axle | Stainless steel |
| | Gear box | Encased crown and pinion, zero maintenance gears. Manufactured in a composite material, ultra-hard-wearing construction with enhanced performance bushings |
| CRESCO | Hopper | 40 litre capacity with front lift point, up to a maximum 45kg weight bearing. 3 drop hole outlets |
| | Impellor | Shaped 24.0 cm four fin impellor. Provides spread width of between 2.5 and 6 metres |
| | Shutter plate (Summer Slider) | Hard wearing multifunctional interchangeable slider. Providing left & right side spread pattern adjustments and a border control system |
| | Shutter plate (Winter slider) | Hard wearing multifunctional interchangeable slider. Providing high output, wide spread and spread width reduction system |
| - | Linkage | Solid steel rod |
| | Agitator | New oscillating spider type, providing superior material movement and reduced drag |
| | On/off control bezel | 1 to 20 scale, with T bar style lever and rate setting lock mechanism |
| | Border Control Lever | 1 - 20 scale, with T bar style lever |
| 7 | Handlebar | Dual shaft to bull horn style handle with cushion grips for ultimate user comfort |
| | Weight empty | 14kg |
| Â | Dimensions | Height 75cm Width 60 cm |
| | Packaging | Semi-Assembled |
| | Pelleting | 120cm by 100cm UK deliveries, 120cm by 80cm EU deliveries, Euro plastic pallets |
| <u> </u> | Box dimensions and weight | Semi-Assembled – 75cm x 58cm x 55cm 14.5 kg |
| | Pallet configuration (units per pallet) | U.K. Assembled 6 Units E.U. Assembled 6 Units |
| | Guarantee/warranty | 2-year limited warranty |
| | Box information | QR code and Bar code, full instruction and how to use manual. Available in different languages |